## **TRESU CFC** Lightweight carbon fiber chamber doctor blade system

8

3

3

Group Ancillary

## **TRESU CFC**

## Carbon fiber chamber doctor blade system

The lightweight carbon fiber chamber doctor blade system offers corrosion resistance, controlled flow and easy handling.

- The carbon fibre composition ensures high-strength chamber qualities
- The design enables ink and coating circulation in relatively low volumes
- The ink-repellent surface offers extra protection against ink and detergents with high and low pH-values
- Curved inner surfaces minimize volume, control discharge, and enable perfect cleaning
- Pressure-control ink and coating circulation
- The chamber prevents solvents from escaping and protects the ink from degradation
- For all printing and coating units
- Easy handling





The TRESU E-Line and P-Line clamping systems enable changeovers of the stainless steel or plastic doctor blades in less than two minutes

Patented TRESU seals ensure perfect sealing

Resistant to acidic, alkaline inks, and cleaning liquids

**TRESU Group** 14-16, Eegsvej DK-6091 Bjert Tel: +45 76 32 35 00 Fax: +45 76 32 35 10

tresu@tresu.com

www.tresu.com

. W

Technical Specifications		
	Profile	D2-D5/E-Line and P-Line
	Weight	From 2,4 kg/m
	Anilox Ø	80 - 400 mm
	Anilox width	Up to 6000 mm
	Construction	Flexi-, Uni-, and MaxiPrint chamber systems
	Print mode	Flow- and pressure mode for water-, UV- or solvent based inks
	Application	All printing and coating machines



The Best Part of Innovation

A-23-GB-02.15